



# DC EV Charger

## Product Catalogue

**XD TEC**

**Shanghai Xundao New Energy Technology Co., Ltd.**  
1799 Songhui West Road, Songjiang District, Shanghai

E-mail: [marketing@shxundao.com](mailto:marketing@shxundao.com)  
Website: <https://xundao.en.alibaba.com>  
<https://www.xteckpower.com>

## Interface Standard:DC/AC



CE UK RoHS  
CA



\*Dual gun with screen display  
floor mounted charging station

## Technical Information

Model	XD-DC-FD60kW	XD-DC-FD80kW	XD-DC-FD120kW	XD-DC-FD160kW	XD-DC-FD180kW
Output Power	60kW	80kW	120kW	160kW	180kW
Basic Functions	Swipe Card、APP、OCPP、Load balancing (optional feature)				
Output Voltage	200-1000V				
Input Voltage	285-475V				
Output Current	0-200A		0-250A		
Input Current	105A	130A	200A	270A	300A
In Connections	3P+N+PE				
Product Size	1700*730*500		1840*795*570		
Package Weight	255	261	296.5	358	
IP Level	IP54				
Gun Rated Current	≤200A		≤250A		
Gun Line Length	5M(Acceptable customization)				
Inlet Length	0M(Acceptable customization)				
Display	7 inch				
Charging Protocol	GBT27930 / CHADEMO 2.0 / DIN 70121 OCPP 1.6(JSON) / ISO 15118				

## Interface Standard:DC/AC



CE UK RoHS  
CA



## Technical Information

Model	XD-DC-FX160kW	XD-DC-FX180kW	XD-DC-FX240kW
Output Power	160kW	180kW	240kW
Basic Functions	Swipe Card、APP、OCPP、Load balancing (optional feature)		
Output Voltage	200-1000V		
Input Voltage	285-475V		260-530V
Output Current	250A		300A
Input Current	270A	300A	400A
In Connections	3P+N+PE		
Product Size	1880*700*530		
Package Weight	384	392	395.4
IP Level	IP54		
Gun Rated Current	≤250A		≤300A
Gun Line Length	5M(Acceptable customization)		
Inlet Length	0M(Acceptable customization)		
Display	7 inch		
Charging Protocol	GBT27930 / CHADEMO 2.0 / DIN 70121 OCPP 1.6(JSON) / ISO 15118		

\*Double Gun Landing Supercharging Station

## Interface Standard:DC/AC



CE UK RoHS  
CA



## Technical Information

Model	XD-DC-DD40kW	XD-DC-DD60kW	XD-DC-DD80kW
Output Power	40kW	60kW	80kW
Basic Functions	Swipe Card、APP、OCPP、Load balancing (optional feature)		
Output Voltage	200-1000V		
Input Voltage	285-475V	260-530V	
Output Current	0-133A	0-200A	
Input Current	63A	105A	130A
In Connections	3P+N+PE		
Product Size	1494*690*350		
Package Weight	168	211	236
IP Level	IP54		
Gun Rated Current	≤133A	≤200A	
Gun Line Length	5M(Acceptable customization)		
Inlet Length	0M(Acceptable customization)		
Display	7 inch		
Charging Protocol	GBT27930/CHADEMO 2.0/DIN 70121 OCPP 1.6(SON)/ISO 15118		

\*Dual gun ground charging station

## Interface Standard:DC/AC



CE UK RoHS  
CA



## Technical Information

Model	XD-DC-FQ60kW	XD-DC-FQ80kW	XD-DC-FQ120kW	XD-DC-FQ160kW	XD-DC-FQ180kW
Output Power	60kW	80kW	120kW	160kW	180kW
Basic Functions	Swipe Card、APP、OCPP、Load balancing (optional feature)				
Output Voltage	200-1000V				
Input Voltage	285-475V				
Output Current	0-200A		0-250A		
Input Current	105A	130A	200A	270A	300A
In Connections	3P+N+PE				
Product Size	1880*700*530				
Package Weight	294	300	335.5	366	384
IP Level	IP54				
Gun Rated Current	≤200A		≤250A		
Gun Line Length	5M(Acceptable customization)				
Inlet Length	0M(Acceptable customization)				
Display	7 inch				
Charging Protocol	GBT27930 / CHADEMO 2.0 / DIN 70121 OCPP 1.6(JSON) / ISO 15118				

\*Front mounted dual gun ground charging station

## Interface Standard:DC



CCS1



CCS2



CHAdeMO



GBT



CE UK CA RoHS



## Technical Information

Model	XD-DC-WD7kW	XD-DC-WD15kW	XD-DC-WD20kW	XD-DC-WD30kW	XD-DC-WD40kW
Output Power	7kW	15kW	20kW	30kW	40kW
Basic Functions	Plug and Charge、Swipe Card、APP、OCPP、Load balancing (optional feature)				
Output Voltage	50-750V	200-1000V			
Input Voltage	100-280V	280-500V			
Output Current	0-20A	0-60A		0-100A	0-133A
Input Current	32A			49A	63A
In Connections	L+N+PE	3P+N+PE			
Product Size	450*340*165	660*470*248		660*540*280	
Package Weight	—	61.1	73	87.75	
IP Level	IP54				
Gun Rated Current	≤20A	≤50A	≤67A	≤100A	≤133A
Gun Line Length	5M(Acceptable customization)				
Inlet Length	0M(Acceptable customization)				
Display	5 inch				
Charging Protocol	GBT27930 / CHADEMO 2.0 / DIN 70121 OCPP 1.6(JSON) / ISO 15118				

\*Flat single gun wall mounted charging station

## Interface Standard:DC



CE UK CA RoHS



## Technical Information

Model	XD-DC-WD (D) 40kW	XD-DC-WD (D) 60kW
Output Power	40kW	60kW
Basic Functions	Plug and Charge、Swipe Card、APP、OCPP、Load balancing (optional feature)	
Output Voltage	150-1000V	
Input Voltage	285-475V	260-530V
Output Current	0-133A	0-200A
Input Current	63A	105A
In Connections	3P+N+PE	
Product Size	1025*725*625	
Package Weight	121.6	138.2
IP Level	IP54	
Gun Rated Current	≤133A	≤200A
Gun Line Length	5M(Acceptable customization)	
Inlet Length	0M(Acceptable customization)	
Display	5 inch	
Charging Protocol	GBT27930 / CHADEMO 2.0 / DIN 70121 OCPP 1.6(JSON) / ISO 15118	

\*Flat dual gun wall mounted charging station

## Interface Standard:DC/AC



CE UK CA RoHS



\*Mobile charging station



## Technical Information

Model	XD-DC-MD7kW	XD-DC-MD15kW	XD-DC-MD20kW	XD-DC-FD30kW	XD-DC-MD40kW
Output Power	7kW	15kW	20kW	30kW	40kW
Basic Functions	Plug and Charge、APP、OCPP、Load balancing (optional feature)				
Output Voltage	50V-750V	200-1000V			
Input Voltage	100-280V	280-500V			
Output Current	0-20A	0-60A		0-100A	0-133A
Input Current	32A			49A	63A
In Connections	L+N+PE	3P+N+PE			
Product Size	450*310*150	530*320*200		550*370*210	
Package Weight	37.1	43.55	44.95	50	60
IP Level	IP54				
Gun Rated Current	≤20A	≤50A		≤100A	
Gun Line Length	5M(Acceptable customization)				
Inlet Length	0M(Acceptable customization)				
Display	5 inch				
Charging Protocol	GBT27930 / CHADEMO 2.0 / DIN 70121 OCPP 1.6(JSON) / ISO 15118				